



## DATA SHEET

### PRODUCT:

Face Material: **SECURDELAM**  
 Adhesive: **PF2**  
 Backing Paper: **CB74**

ARCONVERT SpA  
 Sede legale e amministrativa:  
 Strada del Linfano, 12  
 38062 Arco (TN), Italy  
 Tel. +39 0464.584444 r.a.  
 Fax Comm. +39 0464.532024  
 Fax Amm. +39 0464.584490  
 Fax Acq. +39 0464.531291

arconvert.com  
 Cap. Soc. €4.000.000 i.v.  
 Codice Fiscale e Registro  
 Imprese n. 01077840682  
 Partita IVA e VAT Code IT  
 n. 01192310223  
 N. Mecc. TN 007450  
 N. REA TN 122101

#### Face Material: **SECURDELAM**

Description: White, opaque, clay coated one side, filled expanded HDPE film.  
 Application: Destructible by laminations. Excellent printing and ink drying. Excellent thermal transfer printing with a very wide range of ribbon. Die-cuts extremely well

Technical Data	Grammage	Caliper	Brightness	Opacity	Glaze	Tensile-strength h MD-CD	Elongation at break MD-CD
	g/m2	micron	%	%	%	Kg/15 mm	%
	60	109	90	92			120-80

#### Adhesive: **PF2**

Description: Acrylic adhesive in water emulsion.  
 Application: Adhesive for plastic films. Good adhesion on apolar surfaces. High resistance to UV rays. High transparency makes this product ideal for "no-label-look" labels. Approved for indirect food contacts and corresponding to UNI-EN 71/3 "toys security" norms.

Technical Data	Tack	Cohesion (min)	Application Temperature (min)	Service Temperature (min)	Service Temperature (max)
	g/25 mm	hours	° C	° C	° C
	900	15	+ 10	-10	+ 100

#### Backing paper: **CB74**

Description: Super calandered glassine paper, siliconised on one side. Colour: WHITE.  
 Application: Backing paper for EDP applications and plastic films in rolls.

Technical Data	Grammage	Caliper	Opacity	Trasparenza	Tensile-strength MC-CD	Elongation at break MD-CD
	g/m2	micron	%	%	N/15mm	%
	74	64		45	100-50	

Date  
14/01/2015

Report  
n° NIN 1062

Revision  
0

Q.C. Manager  
Ing. Sabrina Leoni

All the information and descriptions regarding Arconvert products are based research and are considered reliable, but do not constitute a warranty. Given the extent and constant development of fields of application for Arconvert self-adhesive products, the user must carefully check the suitability of the product for each specific application, bearing all the risks involved. No salesman, agent or representative is authorised to issue guarantees or information other than those contained in this guide which replaces previous editions and information contained herein is subject to change without notice.