



DATA SHEET

ARCONVERT SpA
 Sede legale e amministrativa:
 Strada del Linfano, 12
 38062 Arco (TN), Italy
 Tel. +39 0464.584444 r.a.
 Fax Comm. +39 0464.532024
 Fax Amm. +39 0464.584490
 Fax Acq. +39 0464.531291

arconvert.com
 Cap. Soc. €4.000.000 i.v.
 Codice Fiscale e Registro
 Imprese n. 01077840682
 Partita IVA e VAT Code IT
 n. 01192310223
 N. Mecc. TN 007450
 N. REA TN 122101

PRODUCT:

Face Material: **CAST COATED PRINT**
 Adhesive: **P10P**
 Backing Paper: **KB85**

Face Material: CAST COATED PRINT
 Description: White pure cellulose paper, cast coated on one side with high degree of gloss and exceptional brightness.
 Application: General all-purpose paper, ideal for high quality labels. Excellent printability with all conventional printing systems.

Technical Data	Grammage	Caliper	Brightness	Opacity	Glaze	Tensile-strength h MD-CD	Elongation at break MD-CD
	g/m2	micron	%	%	%	Kg/15 mm	%
	80	88	92	92	83	6,0-3,0	

Adhesive: P10P

Description: Modified acrylic adhesive in water emulsion.
 Application: Adhesive suited to a wide range of applications, featuring high tack and adhesion values as well as good processing properties. Approved for indirect food contacts and corresponding to UNI-EN 71/3 "toys security" norms.

Technical Data	Tack	Cohesion (min)	Application Temperature (min)	Service Temperature (min)	Service Temperature (max)
	g/25 mm	hours	° C	° C	° C
	1200	9	+ 5	- 10	+ 80

Backing paper: KB85

Description: White paper coated and siliconised on one side.
 Application: Backing paper for sheet fed printing systems requiring an excellent dimensional stability.

Technical Data	Grammage	Caliper	Opacity	Trasparenza	Tensile-strength MC-CD	Elongation at break MD-CD
	g/m2	micron	%	%	N/15mm	%
	85	85	84		70-40	

Date
17/04/2004

Report
n° NIN 697

Revision
3

Q.C. Manager
Ing. Sabrina Leoni

All the information and descriptions regarding Arconvert products are based research and are considered reliable, but do not constitute a warranty.

Given the extent and constant development of fields of application for Arconvert self-adhesive products, the user must carefully check the suitability of the product for each specific application, bearing all the risks involved. No salesman, agent or representative is authorised to issue guarantees or information other than those contained in this guide which replaces previous editions and information contained herein is subject to change without notice.