

Technical target values

100% TCF (Totally Chlorine Free)

Grammage (g/m ²) ISO 536	57	60	65	70	75	80	90
Brightness, % ISO 2470 D65	83	83	88	90	90	90	90
Opacity, % ISO 2471	92	93	92	93.5	94	95	96
Gloss, % ISO 8254-1	45	46	62	62	63	63	63
Bulk, cm³/g ISO 534	1.0	1.0	0.9	0.9	0.9	0.9	0.9
L* ISO 5631 D65	90	91	92	93	93	93	93
a* ISO 5631 D65	0.2	0.2	0.4	0.4	0.4	0.4	0.4
b* ISO 5631 D65	-3	-3	-4	-5	-5	-5.5	-5.5

The values given are target values and variations occur.

Producer
SCA Ortviken, Sweden

Areas of applications
Magazines, supplements and inserts
printed in heatset web offset.

Reel diameters
Standard diameters are 100, 120 and 125
cm.

Reel width
The minimum reel width which can be
produced is 400 mm.

Web length
Approximately:

g/m ²	57	60	65	70	75	80	90
Ø 100 cm	15500	14700	14500	13500	12500	11500	10500
Ø 120 cm	22600	21900	21000	19500	18000	17000	16000
Ø 125 cm	24700	23500	23000	21000	19500	18000	16500

Environment

TCF (totally chlorine-free) and certified in accordance with ISO 9001 and 14001. Chain of Custody in accordance with FSC and PEFC.

Wrapping

Reels are wrapped in polyethene laminated liner with inner endshields of corrugated board and polyethene coated outer endshields.

Packing

Reels less than 600 mm in width are always co-packed and marked with a red stripe. We recommend co-packing of reels up to 900 mm.

Surface pH value

The surface pH value of the paper is >6.

Rev. 2013-10-24

For further information and samples, please contact

SCA ORTVIKEN
SCA Graphic Sundsvall AB
Box 846
SE-851 23 SUNDSVALL
www.publicationpapers.sca.com